

## МАШИНА ЗА ДЕЗИНФЕКЦИЈА НА РАЦЕ



- Aluminum main body case
- Lightened advertising part
- Digital display
- Stainless hand cleaning tank
- Fogging nozzle spray
- Liquid motor pump
- Connection records
- Antibacterial liquid bin
- Liquid discharge bin
- Audio and speaker system
- Connection hoses
- Timer electronic circuit
- 5 lt Antibacterial liquid

Машината покрај својата основна употреба за дезинфекција на раце служи и како ефективно маркетинг средство за успешна промоција на Вашиот бренд со поставување на соодветни локации.

Еден уред, две значајни придобивки.



- H14 Aluminum main body case (1.5 mm and 2 mm thickness)
- Black sheet metal bottom flange (10 mm thickness)
- Hinged locked cover (disinfection part)
- Hinged locked cover (digital display part)
- Hinged locked cover (lightened advertising part)
- Electrostatic powder paint (150 micron thickness and baked at 200 degree)
- 2x15w Digital pam 8610 Stereo Amplifier Board (Voltage: DC 9 V-12V operating frequency)  
Output power: 10 w x2 8ohm + 1S w x2 4ohm, Efficiency: 90%, Shutdown Current: 4uA, Quiescent current; 20mA, SNR:86%, Total harmonic distortion: S W / 1 KHz / 8 ---- 0.1%, Frequency range: 20Hz-20 KHz, Input impedance: 1S K, Output Impedance: 4-8, amplifier board size: 30mm \* 2Smm \* 2.Smm
- ISD1820 Voice Recording Playback Module (Working Voltage: 3.3V, Card Dimensions: 37x54mm)
- 12V 5A Metal Case Switch Mode Adapter- MS-60-12 (product dimensions 111\*78\*36)
- LM 7805 Voltage regulator (Output Voltage: 5V, Maximum input voltage: 35V, Minimum input voltage: 7V, Maximum output current: 1A, Output voltage tolerance: 4% for LM7805CT, 2% for LM7805ACT)
- Timer MCB-9, 12-240 VAC / DC
- Pixel Led | Rgb 30 mm 12 Volt
- 12V 5A Double contact, Finder Type (SMI-12VDC-SL-2C)
- 20x10 Junction box for wet environments
- Air Motor, 220V 50Hz 54W 1/1 min. CI 155 Tf 35
- 1/2 Air hose
- 10/6 reduction pneumatic quick connect coupling
- 1/2 disinfection spray hose
- 10-16 connection clamps
- 6 mm 1/4 connection record
- 2 bar fogging nozzle
- M18 photoelectric sensor, diffuse mode (10-30VDC, 200mA)
- Hd Media player (Input: 100-240V, 50 / 60Hz, Consumption: 12W, Usb flash media support)
- AC 110/220V 50/60Hz 12V-5A adapter
- 2,5 row terminal blocks
- 1/4 hose elbow connector
- 12V 0,5W speaker
- Liquid drain device

Напомена: Понудата не вклучува брендирање на уредот и снабдување со батерии. Производите се достапни на лагер од 01.06.2020 година.